

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 58099566 A

(43) Date of publication of application: 13.06.83

(51) Int. Cl

F16K 11/04

(21) Application number: 56195720

(71) Applicant: SAGINOMIYA SEISAKUSHO INC

(22) Date of filing: 07.12.81

(72) Inventor: HIRATA KAZUO

(54) TWO-POSITION OPERATION THREE-WAY VALVE

and (c), and stabilizes the operation of switching between two positions by the ball valve.

(57) Abstract:

PURPOSE: To obtain the stable operation in a captioned valve provided with a ball valve of a magnetic body between two outlet side connecting pipes set horizontally by providing a convex part projected inward at the intermediate part between two connecting pipes for preventing the ball valve from stopping at the intermediate part.

CONSTITUTION: Outlet side connecting pipes B and C made of nonmagnetic bodies are horizontally set, while an inlet side connecting pipe A is connected upward and vertically in an inverse T-shape on the intermediate part between both connecting pipes B and C. In connecting pipes B and C, valve seats (b) and (c) of non-magnetic bodies are respectively fixed by caulking 3 or other processes, and in a horizontal pipeline D between both valve seats (b) and (c), a ball valve 1 made of a magnetic body is rotatably contained for constructing a three-way valve. In this three-way valve, at the bottom of a horizontal pipeline D on the extension of the inlet side connecting pipe A, a convex part 2 is projected to check the stoppage of the ball valve 1. This construction prevents the ball valve 1 from being placed at the center between valve seats (b)

COPYRIGHT: (C)1983,JPO&Japio

